



M.K.S. MACHINERY CO., LTD.

3575/47-48 Soi Chalaemnittr, Pradu 1 Road, Bangclo, Bangkhorlaem, Bangkok 10120, Thailand

E-mail: mail@mksmachinery.com Website: www.mksmachinery.com

Tel: 02-688-4192, 089-893-1715

16SS / 18SS

NST #30 | NST #40

Vertical Milling Machine

Standard accessories

- Draw bar
- Tool box and tools
- Chip cover on Y axis
- Manual lubrication system
- Automatic lubrication system (18SS)
- Turcite B (X/Y)
- Grinding (X/Y)
- Z axis Rapid up/down deluxe type electric box (18SS)



Specification	16SS	18SS
X/Y/Z travel (mm.)	850/426/400	850/426/400
Longitudinal travel (M./A.) (mm.)	850/750	850/750
Cross travel	426	426
Vertical travel (mm.)	400	470
Quill travel (mm.)	127	140
Overarm travel (mm.)	457	540
Dist. from spindle nose to table (mm.)	40-450	90-560
Spindle centerline to column (mm.)	60-620	85-625
Table dimension (mm.)	1270x254	1270x254
T-slots (WidthxNo.xPitch) (mm.)	16x3x63	16x3x63
Max. table load (kgs.)	200	200
Spindle taper type	NT 30	NT 40
Spindle motor	3HP	5HP
Quill Diameter (mm.)	85	105